

# CLOU

ID ECCLU

IP 66



5 YEARS WARRANTY

**CLOU** enlarges with **unlimited creative solutions the outdoor light**. A **bollard, wall** or **ceiling** element, CLOU is designed to illuminate green areas and semi-open spaces with a modern and brilliant design. The structure is composed by an extruded petal profile with three grooves, where you can install silicone strip that, combined with spots, grant you to play in an amazing way with the light. Moreover, an overlapping junction can be applied to CLOU body to allow you to **create a dynamic weaving profile with different directions in the space** to obtain an even more refined and **personalized lighting composition**.

## ☑ Features

- IP 66
- IK 06
- -20°C/+40°C

## 💡 Led

- 3000K
- >108 lm/W; >120 lm/W
- CRI>90
- Eye safety: RG0/RG1
- Mac Adams 3
- L90/B50 >50.000h

## 🕒 Specifications

- Po lens, beam angles: 15°-50°
- Silicone strip 7W/ln

## ☐ Body

- Aluminum with epoxy powder coating

## 🎨 Colors

- White RAL 9003 wrinkled - code W
- Black RAL 9005 wrinkled - code BK
- Corten Bronze - code BC
- Green RAL 6036 - code VR

## ☆ Certifications

- CE Conformity
- Energy efficiency D


## 📦 On request

- 3500K



# CLOU ARM

Extruded aluminum profile.




IP 66

Cod.	L In
ECCLUARM700	27.56"
ECCLUARM1000	39.37"
ECCLUARM2000	78.74"
ECCLUARM3000	118.11"

# CLOU SPOT

PC lens beam angle 15°-50°.  
Single cable entry. Driver built-in.




IP 66

Cod. 3000K	Led	lm	ØIn
ECCLUISP30915	7W 15°	420	1.97"
ECCLUISP30950	7W 50°	420	1.97"

# CLOU SPOT DOUBLE

PC lens beam angle 15°-50°.  
Double spot with cable. Driver built-in.



Cod. 3000K	Led	lm	ØIn
ECCLU2SP30915	7W + 7W 15°	840	1.97"
ECCLU2SP30950	7W + 7W 50°	840	1.97"

# CLOU ROUND STRIP

Silicone Led strip 7W/In.



Cod. 3000K	Led	lm	LIn
ECCLUST30924V87	8W/In	280lm/m	27.55"
ECCLUST30924V810	8W/In	280lm/m	39.37"
ECCLUST30924V820	8W/In	280lm/m	78.74"
ECCLUST30924V850	8W/In	280lm/m	196.85"

# ACCESSORIES



Wall mounting element with end cap.

**ECCLUWMEWEC**



Wall mounting element extension.

**ECCLUWMEE**



Wall mounting element 1 way.

**ECCLUWME1W**



Driver ON/OFF IP 67 24V.

**Tridonic**  
**60W**  
**100W**

---

# TECHNICAL NOTES



*Olou can be used as garden light with different lenght.*



*Can combine spotlight with diffused light.*